RCOMMARU

MX-190CD

MX-1000CD ▶





 $\ensuremath{\mathbb{X}}$ water tank is sold seperately.

Smart jog-dial system



Innovative design raised durability by applying easy operation jog-dial method

- LED indoor light



LED indoor light which can check egg condition

?

Door sensing fucntion



Internal Micro switch which can present temporary temperature rise from door opening and closing

Advanced concept PTC heater humidity unit



Excelent durability and heat efficiency by applying PTC heater and maintenance of safe humidification effect without overheating

0

New egg turning device



Upgraded egg turning device which can roll egg stably



Superb high density foam board



A thick coated sheet for warmth reinforcement and embossing surface treatment to present pollution

AUTOELEX CO.,LTD.



Artificial intelligence Evolution of digital incubator!

CRADLE TYPE MAIN FUNCTIONS

- Convenient jog dial operation for optimized user interface
- ▷ Innovative PTC Heating Type humidifier eliminates bacteria from humidity reservoir
- Increased temperature stability and energy efficiency due to high-density insulated body developed by Rcom
- Built-in 'open door' micro-switch detection
- □ Automatic temperature & humidity control and set function
- Automatic egg turning & turning interval set function (1h, 2h, 3h)
- > FND display for easy recognition of incubation state
- ▷ Artificial intelligence electronic control system by Rcom technology
- > Transparent double insulated viewing window
- Sliding vent to in the chamber
- ▷ Built-in water level sensing switch automatically detect the water level inside the humidifier and alarm water refill is required
- Precise temperature and humidity sensor produced by Sensirion, Swiss (ver. 3rd Generation of Sensirion, Swiss)
- Dependable temperature by Rcom optimum air flow technology



CRADLE TYPE USEFUL FUNCTIONS

- □ Built in LED dome-light for ease of viewing when door is open
- Degree C / degree F interchangeable
- Separate humidifier not required due to built-in humidifier unit within the device
- Warning & display function of abnormal temperature caused by ambient temperature fluctuation
- Incubation data memory and alarm function in case of blackout
- Equipped with water nipple in front for efficient water supply
- Equipped with removable upper cover for convenience of cleaning or maintenance after incubation
- □ Automatic horizontal positioning stop function and manual location adjustment function for effortless tray removal
- Adjustable universal egg trays suitable for a variety of egg sizes (sold separately)
- ▶ Perform separate egg rotations by leve ※ MX-1000CD

CRADLE TYPE OPTION

Universal Egg Basket and ABS Divider (Sold separately)





OPERATIONAL FUNCTIONS

Rcom MARU DELUXE MAX 190 / 380



Rcom MARU DELUXE MAX 1000



- ① Heater Operation Lamp
- 2 Temp. Display
- 3 Humidity Display
- $\textcircled{4} \ \mathsf{Pumping} \ \mathsf{System} \ \mathsf{Operation} \ \mathsf{Lamp}$
- ⑤ Jog Dial
- 6 Doom Light Button (1 second) Horizontal eggs turning button (3 seconds)
- 7 Egg turning Lamp
- **® Water Supplement**
- 9 Function Table
- **10** Outage Notification
- 11 Turning on L Lamp
- 12 Turning on R Lamp

The technology carving out a future

Creation of most valuable life birth!!



IDENTIFICATION OF PARTS

- 1 Air Vent (Top)
- 2 Power Connecting (the rear)
 - For connecting power cord.
- 3 Air inlet vent
- 4 Air Vent (Front)
- **6** Control Panel / Display Window
 - Refer to control panel function description
- **6** Jog Dial
- Nipple for water hose
- **8** LED Room Light
- **9** Temp, Humi. sensor / Door detecting micro switch
- Tray (Cradle Type)
 - 190, 380 : 3Layers(1Role)
 - 1000 : 4Layers(2Roles)
- Door
 - Dual structured insulated window
- Insulation Board
- Universal Egg Basket (Sold Separately)
- Matching Space
 - Temporary space for hatching
- B Rubber foot, Door Guide




BASIC COMPONENTS








Power Cord



Silicon Tube : 1.5M (Diameter: Ø4*6)



SOLD SEPARATELY)



Universal Egg Basket



ABS Divider



Spinning Wheel, Bracket

CRADLE TYPE SPECIFICATION

Name	CT Series model No.	Capacities [Chick egg size]	Egg turning method	Egg turning angle [*]	Egg turning Interval [min]	Humidi fication device	Option	The number of trays	Size (WxLxH) [mm]	Functional ranger	Weight [Kg]	Maximum electric power [W]	Average electric power [W]
Rcom MARU DELUXE MAX 190	MX-190CD	168	Cradle	0, 90° (±5°)	0,60,120,180	0	Egg basket ABS divider	3 floors×1row	425x473x765	temperature: 20~42°C (68~107.6°F) humidity: 20~70%	25	440	70
Rcom MARU DELUXE MAX 380	MX-380CD	336	Cradle	0, 90° (±5°)	0,60,120,180	0	Egg basket ABS divider	3 floors×1row	425x790x765	temperature: 20~42°C (68~107.6°F) humidity: 20~70%	30	440	70
Rcom MARU DELUXE MAX 1000	MX-1000CD	840	Cradle	0, 90° (±5°)	0,60,120,180	0	Egg basket ABS divider	4 floors×2row	845x790x890	temperature: 20~42°C (68~107.6°F) humidity: 20~70%	53	440	70

INTERIOR



Cradle egg turning device



Egg Basket with ABS divider (sold separatly)



Main controller



Water hose connector



Air booster



Slide type Air-vent



PTC Humidifi



Tube clamp



Digital Humi. & Temp. sensor



Duplicated view window




Cradle type tray



Foam board

Airflow simulation



To minimize temp variation inside the incubation Airflow simulation

RCOMMAR DELUXE H&B



MX-380HBD

Digital Hacher&Brooder

Rcom MARU Hatcher & Brooders are designed by computer to build optimal environment inside of machine's air flow and have digital technology for fully automatic function.

MAIN FUNCTIONS

- Convenient jog dial operation for optimized user interface
- ▷ Innovative PTC Heating Type humidifier eliminates bacteria from humidity reservoir
- ▷ Increased temperature stability and energy efficiency due to high -density insulated body developed by Rcom

- > FND display for easy recognition of incubation state
- ▷ Artificial intelligence electronic control system by Rcom technology
- > Transparent double insulated viewing window
- \triangleright Sliding vent to in the chamber
- Built-in water level sensing switch automatically detect the water level inside the humidifier and alarm water refill is required
- Precise temperature and humidity sensor produced by Sensirion, Swiss (ver. 3rd Generation of Sensirion, Swiss)
- Dependable temperature by Rcom optimum air flow technology

USEFUL FUNCTIONS

- \triangleright Built in LED dome-light for ease of viewing when door is open
- Degree C / degree F interchangeable
- ▶ Built-in brooding compartment for convenient management
- Separate humidifier not required due to built-in humidifier unit within the device

RECOMMENDE

▶ Warning & display function of abnormal temperature caused by ambient temperature fluctuation

- Incubation data memory and alarm function in case of blackout
- Equipped with water nipple in front for efficient water supply
- Equipped with upper cover for convenience of cleaning or maintenance after hatching
- □ Built-in internal air filter for equipment protection

Universal Egg Basket and ABS Divider, Basket Support

SPECIFICATION

Name	Model No.	Capacities [Chick egg size]	Functional ranger	The number of trays	Option	Humidification Device	Size (WxLxH) [mm]	Weight [Kg]	Maximum electricpower [W]	Average electric power [W]
Rcom MARU DELUXE H&B 380	MX-380HBD	300~350	temperature: 20~42°C (68~107.6°F) humidity: 20~70%	3 floors×1row	Egg basket + Basket supporter	0	425x790x765	30	440	70

OPTIONAL PARTS



Brooding box (Included)



Rotary wheel, Bracket (sold separatly)




Air-filter



Egg Basket with cover (sold separatly)

OPERATIONAL FUNCTIONS





- ① Heater Operation Lamp
- Temp. Display Humidity Display
- Pumping System Operation Lamp
- ⑤ Jog Dial
- 6 Doom Light Button
 7 Function Table
- Outage Notification
- Warning Lamp

Water Supplement Lamp

Sold separately